WRIGHT FLYERS

August 2017

AUGUST CLUB MEETING

The next Wright Flyers club meeting will be on Saturday, August 26 at 12:00 Noon **at the WF Field**. Food and beverages will be served following the meeting.

MINUTES OF JULY MEETING

There are no minutes, the meeting was cancelled due to weather.

UP COMING EVENTS

- 9/9/2017 - 9/10/2017 - LUMS POND IMAC CHALLENGE. Site: Lums Pond Rc Field. Email: eflightbill@gmail.com Visit: delawarerc.com. Sponsor: DELAWARE RC CLUB
- 9/2/2017 - 9/3/2017 - DWIGHT HUNTER MEMORIAL FLOAT FLY & CHILIFEST. Site: Lake Redman. Visit: yorkrc.com Email: heindelsmarineservices@yahoo.com. Electric aircraft, 2.4 radios only. Rain Date is 9/11/2016.
- 9/23/2017 - 9/24/2017 - CHARM CITY MEMORIAL FLY IN. Site: Swap Modelers Flying Field. Email: artvail@verizon.net Sponsor: SOUTHWEST AREA PARK MODELERS
- 10/7/2016 - SWAPTOBERFEST SWAP MEET. Site: Swap Modelers Flying Field. Visit: www.swaprc.org. Bring some stuff to fly and stuff to sell! Spaces $7 ea (provide your own table and chairs), 9:00 to noon; Sponsor: SOUTHWEST AREA PARK MODELERS
- 10/14/2017 - 10/15/2017 -14TH ANNUAL JJ KORNASKI CHILI FLY. Site: Blue & Gray Club Field. Visit: www.bluegrayrc.com.. Flying 10am until 5pm both days. Tailgating for selling RC items permitted. Concession stand will be open from 11am-2pm. Sponsor: BLUE & GRAY MINIATURE AIRCRAFT

HAPPY BIRTHDAYS

Joesph Litosky - September 1
Robert Guienot - September 11
Edward Mickle - September 27

BLURB

Two elderly couples were enjoying a friendly conversation when one of the men asked the other, "Fred, how was the memory clinic you went to last month?"

"Outstanding," Fred replied. "They taught us all the latest psychological techniques: visualization, association, etc. It was great."

"That's great! And what was the name of the clinic?"

Fred went blank. He thought and thought, but couldn't remember. Then a smile broke across his face and he asked, "What do you call that flower with the long stem and thorns?"

"You mean a rose?"

"Yes, that's it!"

He turned to his wife, "Rose, what was the name of that memory clinic?"

THOUGHT FOR THE DAY

"If ever there is tomorrow when we're not together, there is something you must always remember. You are braver than you believe, stronger than you seem, and smarter than you think." Christopher Robin in *Pooh's Grand Adventure*

TIP OF THE MONTH

LiPo Battery Basics

Understanding the technology and its safe use

by Jay Smith, published on Model Aviation website.

Chargers

It should come as no surprise that if you are going to use LiPo batteries to power your electric aircraft, then a charger designed to charge LiPo batteries is required. Although some RTF aircraft come with basic chargers, we are going to focus on stand-alone chargers that offer more flexibility, and functionality.

When it comes time to purchase your first charger, or possibly a replacement charger, there are many things to consider such as input power, output power (in watts), capability to charge single or multiple battery packs at the same time, number of cells supported, balancing, and computer connectivity (for tracking and updates).

Selecting a charger with an LCD screen is also a good idea so that you can easy and accurately change charging parameters and monitor the charge cycle and the voltage of individual cells.

Input Power

Chargers receive power from alternating current (AC), direct current (DC), or have the option to use either one. An AC charger has a built-in power supply allowing it to be plugged into a wall socket, making it handy to charge batteries anywhere there is an available outlet.

DC power comes by either plugging the charger into a power supply or by connecting it to a battery. This is convenient for charging at the field or at events when electrical outlets are unavailable.

Output Power

Chargers are typically rated in watts. Watts are calculated by multiplying the voltage and the amps. A fully charged 2,200 mAh 3S LiPo battery would have a voltage of 12.6. Charging at 1C, it would draw roughly 28 watts of power (12.6 volts x 2.2 amps = 27.72 watts). As you might expect, charging at a higher C rating will increase the required wattage needed from the charger.

Single and Multiport Chargers

Multiport chargers allow two or more batteries to be connected to the charger and simultaneously charged. The only drawback is that the separate ports on the charger split the available wattage, so a four-port charger might only support 50 watts per channel versus 200 watts that might be supported on a single charger.

Balancing

Balance charging LiPo batteries is essential to getting the most from your batteries by ensuring that the voltage of each individual cell in a pack is equal. Balancing helps prevent single cells from being overcharged or discharged, which can damage the cell and has the potential to cause a fire.

The balancing process will typically discharge the higher-voltage cells to match the lower-voltage cells during the charging process. Balancing can also be done with stand-alone products such as the Astro Flight Blinky LiPo Battery Balancer.

LiPo batteries composed of two cells or more could utilize one of four balancing connectors: XH, EH, HP/PQ, and TP. Some chargers include one or more balancing boards and some have all four on one board. If your charger doesn't have the balancing connector to match your batteries, you can probably purchase one.

Connectors

Beyond the balancing connector, most batteries have a primary connection used to connect the battery to your aircraft and to the charger. This consists of a positive and negative wire with a connector that is usually preinstalled on the battery when purchased. Some batteries come without a connector, allowing the end user choose the connector. (To learn more about connectors, see page 33 of the July 2015 issue of Model Aviation.)

Bullet connectors with one positive and one negative lead are used to connect the charge lead to the charger. On the other end could be a pair of bare wires (requiring that a connector be installed), a preinstalled connector, or multiple connectors.

Read the Instructions

Before using a charger or charging a battery for the first time, thoroughly read the instructions. On a charger with an LCD screen, take time to navigate the menus and learn how to change the charge setting. If the charger includes a USB connection, check online or with the manufacturer to see if there are any firmware or software updates. If so, follow the manufacturer's instructions and update the charger.

Visually inspect the charger to ensure that all of the leads, connectors, fans, etc. are serviceable and working.

Thunder Power provides the following instructions before installing a connector or charging a battery for the first time:

1. Make a visual inspection of the pack. Check for any damaged leads, connectors, broken or cracked shrink covering, puffiness, or other irregularities.

2. Before installing or changing the connector, check the pack's voltage using a digital voltmeter (not your charger). All new packs ship at approximately 3.8 volts to 3.9 volts per cell. For example: A 2S pack should read approximately 7.60 volts to 7.8 volts; a 3S pack should read approximately 11.40 volts to 11.7 volts.

3. If you find any damage to the pack or leads, or the voltage is significantly less for your pack than specified, do not attempt to charge or use the battery. Contact Thunder Power [or your battery's manufacturer] directly as soon as possible.

Storage Charge

If storing a LiPo battery longer than one week, batteries should be stored at 3.8 to 3.9 volts per cell (approximately 50% charged). Storing a LiPo battery fully charged can affect its capacity loss over time. A LiPo battery charged to 4.2 volts per cell and then left on the shelf at room temperature will lose roughly 20% of its capacity in two or three years. Store the same battery at the optimum storage voltage and put it in the refrigerator and it will take approximately 10 years to lose 20% of its capacity.

Many chargers on the market today have a built-in storage charge/discharge function. Chose this option, input the battery parameters, and let the charger do all of the work!

Charge Rate

To get the most from your batteries, manufacturers recommend charging at 1C, even if the battery states it can be charged at 3C or even 5C. Charging at a higher rate throughout the life of a battery will affect the number of cycles you are able to get from the battery.

Think of your charge rate as similar to shipping a package. To get your package faster than standard shipping has a cost associated with it—namely money. The same goes for your batteries. Charging them at higher than 1C will allow the charge process to complete faster; however, it is at the cost of reducing the number of cycles that the battery will provide throughout its serviceable life.

Safely Charging Batteries

The two most common instances of having a LiPo battery vent or catch fire is arguably during the charging process or resulting from a crash. In the case of charging the battery, you can further protect yourself by never charging batteries unattended, charging batteries in an isolated area away from flammable materials, and using some type of device or container that will encompass the flames if a battery were to vent.

Commercially available products include the LiPo Sack, LiPo Bunker, an ammunition can, or concrete blocks. Any device that you use should contain the flames while allowing the gases to vent. In the case of the ammunition can, you can drill small holes in the top to allow venting. If the LiPo is unable to vent, it could cause an explosion.

It is important to have a nearby smoke detector, sand, and fire extinguisher. The detector will alert you if a pack begins to vent. The sand should be used to extinguish a LiPo fire and the extinguisher is to put out any other material that might ignite because of the fire. Household fire extinguishers are not rated for use on a LiPo fire. Class D fire extinguishers can be used for a LiPo battery fire, but they are costly.